



4 1/2" O.D. X 10" LG  
TENON

6.73" OD (AT TOP)

FESTOON INSTALLED 90° FROM  
CURB, ON SIDE OPPOSITE THE  
FLOW OF TRAFFIC.

LIGHT POLE SHAFT FABRICATED  
FROM 6063-T4 ALUMINUM TUBE  
(LIGHT POLE ASSEMBLY IS HEAT  
TREATED TO T6 CONDITION AFTER  
WELDING)

10" O.D. X .188" WALL  
(AT BOTTOM)

4"X6" REINFORCED ALUMINUM  
HANDHOLE OPENING WITH  
3/8"-16 HOLE FOR A GROUND  
CONNECTOR AND FLUSH  
FITTING ALUMINUM DOOR

CAST ALUMINUM ANCHOR BASE

ø1'-10"

N.T.S

MODEL NO.: 230667106T4V, 3DR12520G, 4.5"ODX10"LG  
MATERIAL: ALUMINUM ALLOY  
FINISH: RP99P024 - FRANKLIN GREEN 80% GLOSS

POLE TYPE A  
CATALOG #'S:  
POLE RTFA2310-3DR12520G-EA-RP99P024  
BASE COVER: AT22CACSB-RP99P024  
ARM: RBC51/1-CA/RP99P024  
ANCHOR BOLTS: AB-27-4  
STANDARD MATERIAL  
FITTER: GWLF200SCACMC  
LUMINAIRE: MPL2P30S40KASCMTG3P, 4000K LAMP  
LUMEN COLOR

POLE TYPE B  
CATALOG #'S:  
POLE RTFA2310-3DR12520G-EA-RP99P024  
BASE COVER: AT22CACSB-RP99P024  
ARM: RBC51/1-CA/RP99P024  
ANCHOR BOLTS: AB-27-4  
STANDARD MATERIAL  
FITTER: GWLF200SCACMC  
LUMINAIRE: MPL2P30S40KASCMTG3PRPCS,  
4000K LAMP LUMEN COLOR

NOTE: THIS DETAIL TO BE USED IN DOWNTOWN  
FRANKLIN GATEWAY CORRIDORS AND CONNECTOR  
STREETS.

# CITY OF FRANKLIN

STREETSCAPE LIGHT POLE (TYPE A AND B)

**DWG. NO. L-2**

EFFECTIVE DATE: 7/1/2017

*Paul P. Hoyle* 7/1/2017  
CITY ENGINEER DATE

*Stephanie M. Martin* 7/1/2017  
ASST. DIRECTOR OF ENG. DATE