



MODEL NO.: 230667106T4V, 3DR12520G, 4.5"ODX10"LG
 MATERIAL: ALUMINUM ALLOY
 FINISH: RP99P024 - FRANKLIN GREEN 80% GLOSS

NOTE: THIS DETAIL TO BE USED IN DOWNTOWN FRANKLIN GATEWAY CORRIDORS AND CONNECTOR STREETS.

4 1/2" O.D. X 10" LG TENON

6.73" OD (AT TOP)

FESTOON INSTALLED 90° FROM CURB, ON SIDE OPPOSITE THE FLOW OF TRAFFIC.

LIGHT POLE SHAFT FABRICATED FROM 6063-T4 ALUMINUM TUBE (LIGHT POLE ASSEMBLY IS HEAT TREATED TO T6 CONDITION AFTER WELDING)

10" O.D. X .188" WALL (AT BOTTOM)

4"X6" REINFORCED ALUMINUM HANDHOLE OPENING WITH 3/8"-16 HOLE FOR A GROUND CONNECTOR AND FLUSH FITTING ALUMINUM DOOR

CAST ALUMINUM ANCHOR BASE

N.T.S

"RESERVED FOR FUTURE"

CITY OF FRANKLIN

STREETSCAPE LIGHT POLE (TYPE B)

DWG. NO. L-3

EFFECTIVE DATE: 7/1/2017

Paul P. Hoyle 7/1/2017
 CITY ENGINEER DATE

Jonathan M. Weston 7/1/2017
 ASST. DIRECTOR OF ENG. DATE