



**GENERAL NOTES**

1. PLACE PAVERS IN PATTERNS PER CITY OF FRANKLIN STREETScape PLANS. PLACE PAVERS WITH HAND TIGHT JOINTS NOT TO EXCEED 1/8" (MIN 1/16"). SAW CUT PAVERS AS NEEDED TO MAINTAIN ABOVE JOINT TOLERANCES.
2. DO NOT USE FILLERS TO FILL JOINT VOIDS OF EXCESSIVE WIDTH. RESET AND SAW CUT PAVERS AS REQUIRED TO ELIMINATE EXCESSIVE JOINT WIDTHS.
3. 4" THK POURED CONCRETE BASE ON ALL SIDEWALKS AND 6" THK PURED CONCRETE BASE ON ALL DRIVEWAYS.
4. THIS DETAIL TO BE USED IN DOWNTOWN FRANKLIN GATEWAY CORRIDORS AND CONNECTOR STREETS.

N.T.S

**CITY OF FRANKLIN**

2 1/4" THICK BRICK PAVERS ON CONCRETE BASE

**DWG. NO. SS-2**

EFFECTIVE DATE: 7/1/2017

*Paul P. Hoyle* 7/1/2017  
 CITY ENGINEER DATE

*Stephanie M. Martin* 7/1/2017  
 ASST. DIRECTOR OF ENG. DATE