



GENERAL NOTES

1. FOR SPECIFICATIONS SEE "STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION" OF THE TENNESSEE DEPARTMENT OF TRANSPORTATION, SECTION 702 – CEMENT CONCRETE CURB, GUTTER AND COMBINED CURB AND GUTTER.
2. CONCRETE EXPANSION JOINT MATERIAL IS TO BE 1/2" RUBBERIZED EXPANSION JOINT FILLER IN ACCORDANCE WITH SECTION 905 – JOINT MATERIALS OF THE STANDARD SPECIFICATIONS.
3. CONTRACTION JOINTS ARE TO BE SPACED AT 10 FEET. THE SPACING OF 10 FEET MAY BE REDUCED FOR CLOSURES, BUT NOT LESS THAN 6 FEET
3. EXPANSION JOINTS ARE TO BE PLACED AS FOLLOWS: AT TANGENT JOINTS OF CIRCULAR CURBS, BETWEEN CURBS AND ABUTTING RIGID OBJECTS, AT OTHER PLACES WHERE STRESSES MAY DEVELOP, SO AS TO LINE UP WITH PAVEMENT JOINTS WHERE THE ADJACENT PAVEMENT IS CONCRETE MAXIMUM SPACING IS TO BE 100 FEET

N.T.S

CITY OF FRANKLIN

ARTERIAL AND COLLECTOR CURB AND GUTTER

DWG. NO. RP-1

EFFECTIVE DATE: 7/1/2017

Paul P. Hoyle 7/1/2017
CITY ENGINEER DATE

Stephanie M. Martin 7/1/2017
ASST. DIRECTOR OF ENG. DATE