



PAVEMENT SCHEDULE

- ① 1.5" – BITUMINOUS SURFACE COURSE
411-02.10 ACS MIX(PG70-22) GRADING D
- ② TACK COAT
403-01 BITUMINOUS MATERIAL FOR TACK COAT (TC) @0.02 GAL/SY
- ③ 3" – BITUMINOUS AGGREGATE BASE
307-02.08 ASPHALT CONCRETE MIX (PG70-22)(BPMB-HM) GRADING B-M2
- ④ 4" – BITUMINOUS AGGREGATE BASE
307-02.01 ASPHALT CEMENT MIX BASE (PG70-22) BPMB-HM GRADING "A" (APPROX 460 LBS/SY)
- ⑤ PRIME COAT
402-01 BITUMINOUS MATERIAL FOR PRIME COAT (PC) @0.30-0.35 GAL/SY
402-02 AGGREGATE FOR COVER MATERIAL (PC) @8-12LBS/SY
- ⑥ 10" MINERAL AGGREGATE BASE 303-01 MINERAL
303-01 MINERAL AGGREGATE, TYPE "A" BASE, GRADING"D"

GENERAL NOTES

- 1. MAXIMUM SIDESLOPE WHETHER IN CUT OR FILL IS TO BE 3:1.
- 2. ASPHALT THICKNESSES ARE MINIMUMS. THICKNESSES TO BE DETERMINED BY GEOTECHNICAL DESIGN.
- 3. REFERENCE TDOT STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION

N.T.S

CITY OF FRANKLIN

MAJOR AND MINOR COLLECTOR

DWG. NO. RD-2

EFFECTIVE DATE: 7/1/2017

Paul P. Hoyle 7/1/2017
CITY ENGINEER DATE

Stephanie M. Martin 7/1/2017
ASST. DIRECTOR OF ENG. DATE